

Index

Access Control

Stand Alone Access Control
Stand Alone Access Control

Keypad
Audio Intercom
Video Intercom
Proximity
2 Door Proximity & Keypad
Proximity Accessories
Networked Proximity Access
Networked Proximity Access

Gate & Garage Door Automation
Gate & Garage Door Automation

Gate Motor
Remotes
Time recording and attendance solutions
Time recording and attendance solutions

Key Safe
Key Safe

Locking Devices
Locking Devices

Knock N' Lock
Metal Detectors
Metal Detectors

Knock N Lock
Knock N Lock

Guard Moinitering Units
Guard Moinitering Units

Hardware & Accessories
Hardware & Accessories

Door Closers
Striker Locks
Magnetic Locks
Push Buttons & Detectors
Power Supplies

Stand Alone Access Control

GSC



180-10 - GSC PIN-Lock Stand-alone Keypad

- For 800 Users Programmable from the keypad
- Stores 800 unique up to 10 digits PIN codes
- 3 LEDs and sounder
- Multiple selectable outputs (Switch, CCTV)
- Alarm outputs (tamper, forced door, door open or lockout)

- Tamper switch
- Toggle or Pulse mode
- Simple default settings for quick installation
- Ordering no. 71180-10

180-20 - GSC PIN-Lock Plus Stand-alone Keypad with RS232 Port - incl. RS232 connection cable and Windows software



- For 800 Users Programmable from the keypad
- Stores 800 unique up to 10 digits PIN codes
- Battery backed real time clock
- 3 LEDs and sounder
- Multiple selectable outputs (Switch, CCTV)
- Tamper switch
- Toggle or Pulse mode
- Simple default settings for quick installation
- Memory to store 4000 transactions with date & time
- Alarm outputs (tamper, forced door, door open or lockout)
- Ordering no. 71180-20

VISIONLINE

Smartguard - Stand alone keypad



- Up to 1000 unique 1-10 digit codes
- Memory backup facility
- Multiple outputs, various alarm conditions
- Up to 1000 unique 1-10 digit codes - Memory backup facility
- Multiple outputs
- Various alarm conditions
- Weatherproof
- Backlit keys
- Ordering no. 77SMARTGUARD

Audio Intercom

HYUNDAI



304MF - Metal Door Station

- 4 Push Buttons
- Metal Covered
- Flush Mount
- Fits into STD 2 x 4 box
- Ordering no. 63HDR-304MF



HDIP-300PS - Audio Door Phone Kit with 2 Internal Units

- 1 x Plastic Door Station and 2 x Room Station (Master & Slave intercommunication)
- 220V Operational
- 2-Wire installation
- Max. 300m wiring distance
- Intercommunicating internal units
- Remote door open function
- Ordering no. 63AUDIO1-2KIT



HDP-200 - Room Station

- 2 Wire installation
- Expandable up to 3 room stations + 1 door station
- 220V Operational
- Max. 300m wiring distance
- Remote door open function
- Electronic chime call sound
- Ordering no. 63HDP-200



HDP-200/HDR-201P - Audio Door Phone Kit

- 1 x Plastic Door Station and 1 x Room Station
- 2-Wire installation
- 110V or 220V Operational
- Surface mount type
- Electronic chime call sound
- Open door with door lock from room station
- Ordering no. 63AUDIO1-1KIT



HDR-301MF - Metal Door Station

- 1 Push Button
- Metal Covered
- Flush Mount
- Fits into STD 2 x 4 black box
- Ordering no. 63HDR-301MF

Video Intercom

HYUNDAI



HA-300 - 4" B/W Monitor Station

- 4 wires
- Wall mount
- Intercom function between monitors and video memory compatible
- Max 2 Doors and 4 Monitors
- Door release function
- Ordering no. 63HA-300



HAC-300 - 4" Color TFT Monitor Station

- 4 wires
- Wall mount
- Intercom function between monitors and video memory compatible
- Max 2 Doors and 4 Monitors
- Door release function
- Ordering no. 63HAC-300



HCB-150E - 1/3" Plastic Camera

- Surface Mount Surface Mount
- 0.1 Lux in HCB-150E B/W camera model
- 1.0 Lux in HCC-150E Colour camera model
- Fixed camera angle
- Ordering no. 63HCB-150E



HCB-500 - 1/3" Metal Coated Pinhole Camera

- 5EA x Infrared LED
- Flush Mount
- Fits into STD 2 x 4 Box
- 0.1 Lux in HCB-500 B/W camera model
- 1.0 Lux in HCC-500 Colour camera model
- Ordering no. 63HCC-500



HCB-703 - 1/3" B/W Aluminum Coated Camera

- Flush Mount
- 6EA x Infrared LED with 3 push buttons
- For 3 Family Houses
- Ordering no. 63HCB-703



HCC-150E - 1/3" Plastic Camera

- Surface Mount Surface Mount
- 0.1 Lux in HCB-150E B/W camera model
- 1.0 Lux in HCC-150E Colour camera model
- Fixed camera angle
- Ordering no. 63HCC-150E



HCC-500 - 1/3" Metal Coated Pinhole Camera

- 5EA x Infrared LED
- Flush Mount
- Fits into STD 2 x 4 Box
- 0.1 Lux in HCB-500 B/W camera model
- 1.0 Lux in HCC-500 Colour camera model
- Ordering no.63HCC-500



HCC-703 - 1/3" Color Metal coated Camera

- Flush Mount
- 3 Push Buttons
- For 3 family Houses
- White LED
- Ordering no. 63HCC-703



HDP-3000 - Expandable Audio Interphone

- Expandable up to 1 unit HA/HAC-300 and 3 units HDP-300
- Powered from Monitor Station
- Intercommunication between units
- 2 Call chimes (door to room, room to room)
- Remote door open function
- Ordering no. 63HDP-3000



HVM300B - Video Image Memory

- 64 Image Cuts (for HA-300)
- Ordering no. 63HVM-300B



HVM300C - Video Image Memory

- 64 Image Cuts (for HA-300)
- Ordering no. 63HVM-300C

Proximity

GSC



625-10 - Proxswitch

- Controls access for up to 20 Users
- Adding and deleting tags is done by simple use of a Master Card
- Simple programming via Mastercard
- Optional 631-10 Tag Simulator allows deleting of lost tags
- Reading range: Tag 50mm, Card 100mm
- Units includes master card and 4 key ring tags
- Pulse mode or toggle mode
- Waterproof to IP66
- LED status indication
- Ordering no. 71625-10

630-10 - ProxLock - 120 Users



- Controls access for up to 120 users in 630-10
- Simple to program
- Read range 60 - 100mm depending on type of tag used
- Read from front or back of the unit
- Three LEDs indicate status
- Optional 631-10 Tag Simulator allows programming and deleting of lost tags
- Optional transaction buffer module and Win-Software
- Optional Remote Reader Head for opposite side of door
- Relay incorporated in unit
- Wide range of input voltages
- Pulse or Toggle mode
- Ordering no. 71630-10

630-15 - ProxLock - 500 Users



- Controls access for up to 500 users in 630-15
- Read range 60 - 100mm depending on type of tag used
- Read from front or back of the unit
- Three LEDs indicate status
- Wide range of input voltages
- Pulse or Toggle mode
- Optional transaction buffer module and Win-Software
- Optional Remote Reader Head for opposite side of door
- Ordering no. 71630-15

630-20 - ProxLock for up to 2000 tags



- Controls access for up to 2000 users in 630-20
- Read range 60 - 100mm depending on type of tag used
- Read from front or back of the unit
- Three LEDs indicate status
- Wide range of input voltages
- Pulse or Toggle mode
- Optional transaction buffer module and Win-Software
- Optional Remote Reader Head for opposite side of door
- Relay incorporated unit

- Ordering no. 71630-20

631-10 - ProxLock Tag Simulator



- Optional programming device for ProxLock
- Allows adding or deleting cards and tags
- Maintains security by operating together with system Mastercard
- Ordering no. 71631-10



634-10 - GSC ProxLog Data Recording Module

- Optional transaction logging for Prolox units
- 800 transactions wity date and time
- Non volatile memory ensures data protection
- Ordering no. 71634-10



634-20 - GSC ProxLog PC interface cable

- Interface cable to connect one or multiple 634-10 ProxLog recording modules to the PC
- Ordering no. 71634-20



634-50 - ProxLog Windows Software

- Win software to view card holders details and activities with date and time
- Provides record of up to 2000 card holders
- Print card holder and activity reports
- Ordering no. 71634-50

2 Door Proximity & Keypad

650-10 - GSC KeyProx Controller with Windows Software



- 2 Door Access Control System
- Free Windows software
- System programming via keypad or PC
- 1000 Users with optional 1 - 6 digit PIN codes
- 8 Security schedules with time zones
- 3000 transaction stored in controller memory
- Non-volatile memory - 10 year data retention without power
- Exit Pushbutton
- Security levels: PIN only, Card only, Card + PIN, Double card, Double PIN, Double card + PIN
- Optional alarm inputs and outputs
- Ordering no. 71650-10

650-50 - KeyProx RS232 Cable



- Connects the 650 Controller to the PC
- Cable length: 5m
- Ordering no. 71650-50

651-10 - GSC KeyProx Proximity Reader Head with Keypad



- Reads PIN codes and/or proximity card
- 3 LEDs and sounder
- Supply voltage: 11 - 14 VDC
- IP rating: IP50
- Ordering no. 71651-10

652-10 - GSC KeyProx Proximity Reader Head



- Maximum of two Reader/Keypad or Reader combination
- Reads proximity card
- 3 LEDs and sounder
- Waterproof to IP65
- Ordering no. 71652-10



653-10 - GSC KeyProx Remote Read Head

- One unit can be connected to every 651-10 reader
- Use in place of Request to exit Button
- Waterproof to IP65
- Ordering no. 71653-10

Proximity Accessories

GSC

946-60 - ProxNet Weather Proof Housing



- Use for outdoor applications
- Clear polycarbonate lid allows monitoring of LEDs
- Water and Dust proof to IP66
- Tamper protection
- Ordering no.17946-60

PROXIMITY

620-10 - Proximity Key ring tag (Grey)



- Tag Size: 35 x 28 x 6.4 mm
- Drop resistance - 100 times from 2m
- Operating Temperature: -40°C to +80°C
- Read Range (typical): 60 mm; Waterproofed to IP66
- Waterproofed to IP66
- Printed card number
- Ordering no. 71620-10

620-20 - Proximity key ring tag (Black)



- Tag Size: 48 x 38 x 6.5 mm
- Drop resistance - 100 times from 2m
- Operating Temperature: -40°C to +80°C
- Read Range (typical): 50 mm
- Waterproofed to IP66
- Printed card number
- Ordering no. 71620-20

620-30 - Prox Card. White credit card type



- Suitable for sublimation printing (both sides)
- Printed card number
- ISO Size: 85.6 x 54 x 0.85 mm
- Drop Resistance: 100 times from 2m`
- Operating temperature: -40°C to +80°C°
- Read Range (typical): 120mm
- Waterproofed to IP66
- Ordering no. 71620-30

620-80 - Prox Card. White 1.1mm thick with slot for card clip



- Card Size: 85.6 x 54 x 1.2 mm
- Drop resistance - 100 times from 2m
- Operating Temperature: -40°C to +80°C
- Read Range (typical): 100mm
- Waterproofed to IP66
- Ordering no. 71620-80

641-71 - ProxNet Diagnostic Card



- Useful installation tool for Installers and for fault finding
- When presenting the Diagnostic Card to a reader, the reader LEDs indicate the readers address
- Card Size: 85.6 x 54 x 1.1 mm
- Ordering no. 71641-71

Networked Proximity Access

GSC

110-10 - Random search generator



- Provides a Search and Pass condition passed on a pre-set percentage chance of search
- Percentage chance of search can be set 0% to 99%
- Visible and Audible indication for search and pass
- Adjustable timer for LED, alarm and relay operation
- Power 12 - 15 VDC
- Ordering no. 71110-10

311-20 - ProxNet RS232/RS 485 Interface/Repeater



- Use to connect ProxNet system to PC
- Use as RS485 Repeater to increase cable length above 1000m or Star configurations
- Provides electrical isolation between input and output
- 220Volt AC
- Ordering no. 71311-20

311-50 - ProxNet RS 485 Repeater/Interface



- Use to connect ProxNet system to PC
- Use as RS485 Repeater to increase cable length above 1000m or between buildings or star configur
- Intelligent unit with microprocessor
- Analyses data packets and rejects corrupted data
- Offers electrical isolation between two RS485 networks
- Provides electrical isolation between input and output
- Power requirements 12Volt DC
- Ordering no. 71311-50

640-31 - ProxNet Proximity Reader



- Models: 640-30 black, 640-31 grey
- RS485 connection (2 wires)
- N/O and N/C relay contacts rated 3AN/O and N/C relay contacts rated 3A
- 3 LEDs and sounder
- Tamper switch
- Exit Pushbutton
- Reader buffer for 1800 transactions in the event of comms failure
- 12V AC or DC supply (75 mA)
- Alarm input
- Door Sense switch input
- Ordering no. 71640-31

640-51 - ProxNet Remote head (Grey)



- Use for Secure Access Control Points
- One unit can be connected to the 640-30/31 Reader
- Models: 640-50 black, 640-51 grey
- 3 LEDs
- Weatherproof to IP66
- Fully potted
- Tamper proof
- Ordering no. 71640-51

640-60 - GSC ProxNet Mini Reader



- Models: 640-60 black, 640-61 grey
- Small and Attractive design
- Excellent read range (130mm with ISO card)
- Requires 1 x 649-10 Reader Interface
- Simple installation up to 50m from Interface
- Water and Dust proof to IP66
- Tamper protection
- Ordering no. 71640-60

640-91 - ProxNet Software



- User friendly windows environment
- Windows Software for Win 95/98/2000/NT/XP
- Simple system administration (add, edit, delete card holders, access levels, time zones, readers, are
- Detailed transaction reports
- Reports can focus on specific areas, readers, single or group of card holders and time & date frames
- Time and Attendance report option
- Export clocking files
- Reader and System Alarm reports
- Absenteeism report
- Ordering no. 71640-31

640-95 - ProxNet Photo ID Software module



- Photo ID add on module for 640-91 software
- Enhances security
- Displays card holders image (photo ID) when a card is read by a selected reader
- Capture card holders photo with USB camera
- Add photos to card holder data base
- Ordering no. 71640-95

641-40 - ProxNet Controller



- Only 1 Controller required per system
- Can be used Off-line and On-Line
- Optional Win software with Password Protection
- Controls up to 254 Readers/devices Controls up to 254 Readers/devices
- Supports 4000 card holders (optional 20 Readers & 6000 card holders)
- Up and down counters
- 65535 transactions stored in nonvolatile memory
- Evacuation function
- Full and timed Anti Pass Back
- 64 Access Level and 64 Areas
- Ordering no. 71641-40

642-10 - ProxNet Display Reader (Black)



- Reader with LCD display required for Time & Attendance Applications
- Displays date and time plus card number
- RS485 connection (2 wires)
- N/O and N/C relay contacts rated 3A
- Tamper Switch
- Alarm input
- Door Sense switch input
- Exit Pushbutton
- Ordering no. 71640-31



647-20 - ProxNet Long Range Reader

- Require Reader Interface
- Ordering no. 71647-20



647-40 - GSC ProxNet Fingerprint Reader

- For Long Read Range applications like Outdoor parking entrance
- Reads through walls
- Typical Read Range ISO card 660mm Tag 300mm
- Requires 1 x 649-10 Reader Interface
- Supplied with 220V power supply
- Waterproof to IP65 (fully potted)
- Operating temperature: - 10°C to 65°C
- Ordering no. 71647-40



648-40 - ProxNet Mini Remote Head

- Models: 648-40 black, 648-41 grey
- Use for Secure Access Control Points
- One unit can be connected to the 640-30/31 Reader
- 3 LEDs
- Weatherproof to IP66
- Fully potted
- Tamper proof
- Also suitable for use with 630 ProxLock
- Ordering no. 71648-40



649-10 - ProxNet Interface

- Used with the following ProxNet products:
- 640-60 ProxNet Miniature Reader Head
- 684-10 ProxNet Mini Reader Head
- 647-40 ProxNet Fingerprint Reader
- 12 Volt DC
- Ordering no. 71649-10

649-30 - ProxNet Card Collector Interface



- Mini Reader
- Relay rated: 5A - 250VAC; 10A - 12 VDC
- 11-14 VDC 50mA
- Operating temperature: 20°C to 65°C
- Use to connect a 947-10/20 Card Collector and 640-60/61
- Ordering no. 71649-30

649-40 - ProxNet Rolling Code Interface



- Use to connect 1 x 740-10 Secure Receiver
- Relay rated: 5A - 250VAC; 10A - 12 VDC
- 11-14 VDC 50mA
- Operating temperature: 20°C to 65°C
- Ordering no. 71649-40

684-10 - ProxNet Mini Reader Head



- Use with 647-40 Fingerprint Reader and 649-10 Reader Interface
- Small and Attractive design
- Excellent read range (160mm with ISO card)
- 3 LEDs and sounder
- Water and Dust proof to IP66
- Tamper protection, fully potted
- Ordering no. 71684-10

699-20 - ProxNet Surge Protector



- Used between the ProxNet RS-485 network and readers & repeaters
- Protects from harmful induced voltage spikes and current surges
- Waterproofed and fully potted
- Ordering no. 71699-20

732-10 - Keyboard Wedge



- Quick and easy way to capture card/tag numbers into the PC software
- Installation takes seconds simply plug in to PC
- Prevents incorrect capturing of card numbers
- Connects to PC via the keyboard port
- Power supplied by PC
- Ordering no. 71732-10

740-10 - ProxNet Secure Receiver



- Connect to ProxNet using 1 x 649-40 Rolling Code Interface
- Keeloq technology for enhanced security
- Rolling code encrypted data
- Operating frequency 433.92 MHz
- Ideally suited for car park access control
- Up to 10m read range
- Internal antenna
- Jumper selection to response to button 1 or 2
- Ordering no. 71740-10

741-10 - ProxNet Key Ring Transmitter



- Two Button control for separate entry and exit
- Read Range: 10 m (depending on installation)
- Operating temperature: - 20°C to 65°C
- Ordering no. 71741-10

741-20 - ProxNet Key Ring Transmitter with Proximity Tag



- Two Button control for separate entry and exit
- Read Range: 10 m (depending on installation)
- Embedded RFID Tag allows the unit to be used with normal proximity readers
- Operating temperature: 20°C to 65°C
- Ordering no. 71741-20

800-10 - ProxNet Pro Networkable Access Control System



- The computers and controllers are networked using industry standard ethernet and may be interconnected by using the site's existing computer network
- 10,000 Controllers
- 20000 Permissions (Access Levels) each with unlimited timezones
- Timezones definable to apply to Days of Week and Holiday
- Permissions (Access Levels) can relate to Areas, Area Groups, Readers and/or Reader Groups
- Access Type - Card only, Card + PIN or PIN Record # + PIN
- Card Expiry by time and date
- Multi-Tenant feature allows partitioning of the system
- Support for PIN keypads with 3 - 8 digit PIN
- Existing ProxNet readers can be bootloaded with new firmware
- Ordering no. 71800-10

810-10 - ProxnetPro RS-485 Reader



- Uses CP series cards and tags
- Connects directly to the RS-485 network - protection and line termination are incorporated
- Operating temperature range: -20°C - +60°C
- RF Frequency: 125 kHz
- Typical reading range: keyring tag - 60 mm, ISO card - 120mm
- Inputs for Exit Pushbutton and Door Switch
- Door strike output capable of switching 2 A
- Ordering no.71810-10

811-10 - ProxnetPro Reader



- Typical current 80 mA typical (excluding external loads)
- Relays - single pole change over voltage free contacts
- Unit has 3 LEDs to indicate polling, access granted or denied
- IP Rating : IP50
- Operating temperature range: -20°C - +60°C
- Large Housing
- Ordering no. 71811-10

812-10 - ProxnetPro Active Readhead



- IP Rating: IP65
- Dimensions: reader 89 x 45 x 16 mm, optional spacer plate 89 x 45 x 7 mm
- 6 way cable: 1m long
- Operating temperature range: -20°C - +60°C
- Reader has 3 LEDs and sounder
- Typical reading range: keyring tag - 60 mm, ISO card - 100mm
- Connects to the 822-10 interface
- Uses CP series cards and tags
- Ordering no. 71812-10
-

820-10 - ProxnetPro 4-Channel I/O Module



- Contacts rated at: 5A @ 120VAC and 2.5A @ 240VAC for non-inductive loads
- Inputs protected against transients
- Connects directly to the RS-485 network - protection and line termination are incorporated
- Relays - single pole change over voltage free contacts
- Power requirements: 10 -13.6V dc. Current consumption - 150 mA maximum (excluding external loads)
- Operating temperature range: -20°C - +60°C
- Ordering no. 71820-10

822-10 - ProxnetPro Single Door Reader Interface



- Power requirements: 11 -14V dc. Current consumption is 50 mA typical (excluding external loads)
- Relays - single pole change over voltage free contacts
- Contacts rated at: 5A @ 120VAC and 2.5A @ 240VAC for non-inductive loads 3A @ 30VDC for inductive loads.
- IP Rating IP50
- Operating temperature range: -20°C - +65°C
- Ordering no. 71822-10

946-60 - ProxNet Weather Proof Housing



- Use for outdoor applications
- Clear polycarbonate lid allows monitoring of LEDs
- Water and Dust proof to IP66
- Tamper protection

947-10 - ProxNet Visitor Card Collector



- Intelligent card collector that verifies the visitor card / tag
- Models: 947-10 Grey epoxy coated; 947-20 Brushed Stainless Steel
- Operates together with 640-60/61 Mini Reader & 649-30 Interface
- LED indication
- Sound signal (can be disabled)
- Recommended Power Supply: Ref 120-30
- Ordering no. 71947-10

Gate motor

ET

14ET8445 - PC Board for ET8762 and ET8765



- PC boards for ET8762 and ET8765
- Order no: 14ET8445

14ET8770 - M.A.M.I Infrared beam



- Selectable 12VDC or 24VDC Supply
- Range 20 Metres
- Separate Transmitter and Receiver
- Weatherproof design
- Vertical and Horizontal Adjustment Screws
- Potential free N/O and N/C single pole relay output
- Order no: 14ET8770



14ET8835 - ET-500 Anti theft bracket

- ET-500 Anti theft bracket
- Order no: 14ET8835



14ET8852 - Gate motor nylon rack 2m

- Nylon rack for gate motor
- 2m long
- Order no: 14ET8852



14ET8856 - Gate motor steel rack 2m

- Steel rack for the gate motor
- 2m high
- Orde no: 14ET8856



14ET9140-3.2M - DC Blue 3.2m kit 24volt sect

- The DC Blue Garage Door operator automates the domestic trackless tip-up type door and the domestic sectional overhead door
- It has a flip open lid with easy access toto mechanicaland electronic components
- The DC blue is fully compatible with all ET Blue transmitters
- Order no: 14ET9140-32M



14ETRX1-RC - 1 chanel rolling code REC blue

- 1 channel
- 15 Memory codes
- 12-24 volts
- Order no: 14ETRX1-RC

14ETRX3-RC - ET3 CH rolling code rec-blue



- 14ETRX3-RC allows for pulse, latch or unique programmable up to 55sec sustained/delay pulse output.
- Each channel can be configured independently
- 12-24 Volts
- Order no: 14ETRX3-RC

14ETRXCONDO-RC - Rolling code complex rec blue



- The RXcondo has a digital display, any of the 999 users can be edited individually without effect to any other users already programmed into the memory
- The display can be turned off in power save mode.
- Order no: 14ETRXCONDO-RC

14MEIRBSEN - IR short range safety beam



- Selectable 12VDC or 24VDC Supply
- Range 20 Metres
- Separate Transmitter and Receiver
- Weatherproof design
- Order no: 14Mierbsen

ET 8701 - BFT Deimos BT 24VDC Gate Motor with Slide Kit



- 300Kg
- Low Traffic incl. 4m Rack & Battery Back-up Supply
- Includes onboard ET Blue Rolling Code Receiver
- Ordering no. 14ET 8701

ET 8706 - BFT Icaro 220VAC Gate Motor with Slide Kit



- 2000Kg
- Heavy Traffic incl. 4m Rack
- No Battery Back-up Supply
- Ordering no. 14ET 8706



ET 8765 - ET DC500 Gate Motor with Slide Kit

- 500Kg
- Low Traffic incl. 4m Rack & Battery Back-up Supply
- Includes onboard ET Blue Rolling Code Receiver
- Ordering no. 14ET 8765

ET 9145 - DC Blue 2.2m Kit 24Volt Tipon



- For domestic Tip-up type door
- Includes onboard ET-Blue Rolling Code Receiver and 2 TX4 TC Transmitters
- Ordering no. 14ET 9145

ET 9146 - DC Blue 3.2m Kit 24Volt Sectional



- For domestic Sectional type door
- Includes onboard ET-Blue Rolling Code Receiver and 2 TX4 TC Transmitters
- Ordering no. 14ET 9146



ET8762 - ET ACDC500 Gate Motor with Slide Kit

- 500Kg
- Heavy Traffic incl. 4m Rack & Battery Back-up Supply
- Includes onboard ET Blue Rolling Code Receiver
- Ordering no. 14ET8762

Remotes

ET



14ETLTX3 - 14ET3 Channel code learning TX

- 3 button type
- Battery low indication
- 10 - 100m range line of sight
- 433.92 Mhz frequency
- Easily identifiable
- Consistent colour matching across the range
- Durable and robust

- Incorporates the world-renowned keellog rolling-code
- Order no: 14ETLTx3

14ETTX2-RC - 2 Button rolling code TX blue



- 2 button type
- Battery low indication
- 10 - 100m range line of sight
- 433.92 Mhz frequency
- Easily identifiable
- Consistent colour matching across the range
- Durable and robust
- Incorporates the world-renowned keellog rolling-code
- Order no: 14ETTX2-RC

ET TX1-RC - One Button Remote



- 1 button type
- Battery low indication
- 10 - 100m range line of sight
- 433.92 Mhz frequency
- Easily identifiable
- Consistent colour matching across the range
- Ordering no. 14ET TX1-RC

ET TX6-RC - Six Button Remote



- Wireless 2 button handheld transmitter
- Ordering no. 14ET TX6-RC

SHERLOTRONICS



Sherlotronics MB3000P - Mimic Base unit

- Code hopping Mimic Base unit, 403.55Mhz
- Real time date and time logging

- 1000 Transmitters in memory
- Custom 16Character Text
- 400m Range line of site
- LPT1 Printer and RS232 output
- Two Relay outputs
- Buzzer onboard
- Ordering no. MB3000P



Sherlotronics PTX1 - One Button Pendant Remote

- Code hopping handheld Pendant transmitter, 403.55Mhz
- Recommended for wireless Panic button applications
- Ordering no. PTX1



Sherlotronics RX1-100 - Single Channel Receiver 100m

- Code hopping Single Channel Receiver, 403.55Mhz
- 100m Range line of site
- Latching or Momentary relay output
- 12 -24v AC / DC
- Ordering no. RX1-100



Sherlotronics RX1-400 - Single Channel Receiver Long Range

- Code hopping Single Channel Receiver Long Range, 403.55Mhz
- 400m Range line of site
- Latching or Momentary relay output
- Buzzer onboard
- Whip aerial
- Ordering no. RX1-400



Sherlotronics RX4-400 - Four Channel Receiver Long Range

- Code hopping Four Channel Receiver Long Range, 403.55Mhz
- 400m Range line of site
- Latching or Momentary relay outputs
- Buzzer onboard
- Whip aerial

- 12 -24v AC / DC
- Ordering no. RX4-400



Sherlotronics ST4001P - One Button Pendant Remote

- Trinary Dip-switch handheld Pendant transmitter, 403.55Mhz
- Recommended for wireless Panic button applications
- Ordering no. ST4001P



Sherlotronics TX1 - One Button Keyring Remote

- Code hopping handheld transmitter, 403.55Mhz
- 5 year factory warranty
- Ordering no. TX1



Sherlotronics TX2 - Two Button Keyring Remote

- Code hopping handheld transmitter, 403.55Mhz
- 5 year factory warranty
- Ordering no. TX2



Sherlotronics TX4 - Four Button Keyring Remote

- Code hopping handheld transmitter, 403.55Mhz
- 5 year factory warranty
- Ordering no. TX4




Sherlotronics TX6 - Six Button Keyring Remote

- Code hopping handheld transmitter, 403.55Mhz
- 5 year factory warranty
- Ordering no. TX6

Time recording and attendance solutions

GSC



317-01 - TimeMaster Time & Attendance Software

- Versions for 100, 250, 500 and 4000 Employees
- Runs on Win 95/98/2000/NT/XP platform and is net workable
- Password protection
- Export to Payroll packages
- Schedules, rolling schedules, shifts, unlimited shift patterns etc. etc.
- For the extensive list of TimeMaster Time and Analysis features and report samples, please request
- Ordering no. 71317-10

370-10 - MinitMan Time Clock



- A cost-effective electronic timeclock for use with proximity cards / tags
- Two buttons are provided marked IN and OUT for the clocker to select the direction of the clocking
- Non-volatile memory exists in the timeclock to store clockings, bell ringing times, and direction change times
- Communications to a PC may be accomplished via either a RS232 or RS485 port
- A door lock can be connected to the timeclock to provide simple access control
- Ordering no. 71370-10

380-10 - MinitMan-FP Fingerprint Timeclock



- Fingerprint Timeclock prevents unauthorized clocking
- Communication: RS232, RS485 and TCP/IP network
- Operating mode: 1:N (fingerprint only) or ID code plus fingerprint
- Fingerprint templates: 500
- Stored transactions: 30000
- Relay output can be used for access control
- Supplied with MP-Lite basic Time & Attendance software
- Compatible with TimeMaster Time Analysis software
- Ordering no. 71380-10

Key Safe

GE



83-Autoslimline - Slimline S6 with rubber cover and backing plate in auto clamshell packaging

- Easy-to-use keybox
- Small slimline design
- Change combination as often as needed - 1024 different combinations possible
- Holds up to 2 keys
- Enclosing weather cover protects against harsh environmental conditions when mounted on vehicles



86-Touchpoint Cabinet - Key Cabinet Pro - Keyed Lock

- Heavy-duty steel construction
- Enough space for large key rings
- Key cam lock with 2 keys
- Used in large homes or small/medium sized offices
- Available for 30, 60 or 120 keys
- Order no: 86Touchpoint30-Cab



86-Bigbox-S7-Black - Big Box high storage volume design with pushbuttons

- Easy-to-use key box
- Change combination as often as needed - 1024 different code combinations possible
- Large storage space
- A durable weather cover is available to prevent water
- The KeySafe Pro Permanent Big Box is made of zinc alloy
- Order no: 86Bigbox-S7-Black



86-Portable-C3 - Sturdy metal design with protective rubber & pushbuttons

- Easy-to-use portable key box for temporary key storage or use as padlock
- No tools needed for mounting
- Change combination as often as needed - 1024 code combinations possible
- Holds up to 3 keys
- The KeySafe Pro Portable has a durable rubber weather

cover to prevent water intrusion and to hide from obvious water intrusion and to hide from obvious

86-Slimline-S6-White - Easy-to-use keybox



- The KeySafe Pro Permanent Slimline provides convenient,
- Available in multiple neutral colours.
- A durable weather cover is available to prevent water
- Change combination as often as needed - 1024 different combinations possible
- Holds up to 2 keys
- Security level appropriate for residential & small business level appropriate for residential & small business
- Security level appropriate for residential & small business level appropriate for residential & small business
- Order No: 86Slimline-S6-White

86-Strongbox-S5- Over Door Mount - KeySafe Over-the-door-mount provides convenient,



- Easy-to-use key box
- Mount inside doorframes or on top of doors
- Change combination as often as needed - 1024 different code combinations possible
- Holds up to 5 keys
- It can be used to allow quick and easy access to homes, offices, businesses.

86-Strongbox-S5-Clay - StrongBox design with pushbuttons



- Easy-to-use key box
- Security level appropriate for residential & small business applications
- Holds up to five keys
- Change combination as often as needed - 1024 different code combinations possible
- A durable weather cover is available to prevent water intrusion and to hide out of sight.
- Available in multiple neutral colours.
- Order no: 86Strongbox-S5-CLAY

- Available in multiple neutral colours.
- Order no: 86Strongbox-S5-CLAY



86-Touchpoint - TouchPoint keyless pushbutton cam lock w/ bracket & cams

- Heavy-duty die-cast construction
- Change combination as often as needed - 1024 possible combinations
- Clutch mechanism to protect from forced entry
- TouchPoint is designed to replace a standard cam lock in a variety of storage cabinets or enclosures.

Knock N' Lock

ALARMCOM



CM460 - Container Lock Kit

- Installation kit for mounting the SD460 lock on container and truck doors
- Easy installation
- A button for opening from the inside (optional)
- Maximum security - no physical access to lock from outside
- Size: 200mm, 45mm, 45mm
- Housing: Aluminum
- Finish: Silver Aluminum

AS



CL320 - Cylinder Lock (Body)

- Single side or double side clutch system
- Mechanism parts are Stainless Steel made

HD450/455 - Door RIM Lock



- Any wood or metal doors
- Easy installation, no need to drill thru holes in the door
- Button for opening from inside (mechanical)
- Maximum security - no physical access to lock from outside
- Size: 90mm, 63mm, 25.5mm
- Housing: Zamak
- Strike: Stainless Steel Ø 15mm
- Finish: Silver Aluminum
- Power: 123A Lithium Battery
- PC programmable

KK252 - Keypad Knob



- Cylinder Lock Outdoor Knob
- Recommended for commercial applications like offices, airports, hospitals, public buildings, and for private housing (no need to carry a KnockKey)
- Size: Triangle 45mm, 46mm
- Housing: Zamak Die Cast
- Keypad: Tactile Switches, Metallic
- Back Light: Blue
- Power: 123A Lithium Battery

KS300 / 310* - Cylinder Lock (Knob)



- Retrofits all Cylinder Lock applications
- Installation is easy as the installation of a standard mechanical cylinder lock
- Size: Triangle 45mm
- Knob: Zamak Die Cast
- Power: 123A Lithium Battery

MK202 - Mounted Keypad



- Door or frame mounted (indoor only) for use with Door locks or Drawer Locks
- Recommended for commercial applications: Offices, warehouses, airports, hospitals, public buildings, etc. (no need to carry a KnockKey)
- Wireless keypad
- Size: 130mm, 60mm, 23mm

- Housing: Zamak Die Cast
- Back Light: Blue
- Power: 1 or 2X 123A Lithium Batteries

PK117 - KnockKey



- Opens all Knock N'Lock products
- Recommended for consumer and commercial applications
- Size: 56mm, 32mm, 19mm
- Material: PC Plastic injection
- Keypad: Tactile switches, metallic
- Finish: Chrome plating
- Power: CR2 Lithium battery
- PTT: Programmable to transmit pre-programmed code automatic transmission function

SD460/465 - Versatile Lock



- All types of cabinets, containers, or doors
- Easy installation - no wires
- Button for opening from inside (mechanical)
- Maximum security - no physical access to lock from outside
- Size: 185mm, 32mm, 30mm
- Housing: Zamak
- Mechanism : Stainless Steel
- Finish: Silver Aluminum
- Power: 123A Lithium Battery
- Accessories : different types of
- PC programmable

Metal Detectors

VISIONLINE

HMD - Hand Held Metal Detector



- Fully adjustable sensitivity control
- Lightweight and comfortable grip

- De-sense button and tightly controlled detection pattern
- High volume audio alert
- Operate on disposable or rechargeable batteries
- Ordering no. 77HMD

Knock N Lock

KNOCK 'N LOCK



CB460 - Container Door Bolt Kit

- Size: 82mm, 65mm, 39mm
- Housing: Aluminum
- Bolt: Stainless Steel Ø19mm
- Finish: Silver Aluminum
- For container and truck doors
- Easy installation.
- Designed for mounting on top, bottom or hinge side of the door
- Note : The bolt is not activated by Knocks
- Ordering no. 90CB460



CM460 - Container Lock Mounting Kit

- Size: 200mm, 45mm, 45mm
- Strike: Stainless Steel ?15m
- Finish: Silver Aluminum
- Installation kit for mounting the SD460 lock on container and truck doors.
- A button for opening from the inside (optional)
- Maximum security - no physical access to lock from outside
- Excludes SD460 lock
- Ordering no. 90CM460



HD450 - Hinged Door Lock (Opens In)

- Size: 90mm, 63mm, 25.5mm
- Housing: Zamak
- Finish: Silver Aluminum
- Strike: Stainless Steel Ø15mm
- Power: 123A Lithium Battery

- Easy installation, no need to drill thru holes in the door
- PC programmable in HD455 model
- Maximum security - no physical access to lock from outside
- Ordering no. 90HD450

KA700 - Knock Code Activator, 123A Lithium Battery Operated



- Can be installed to activate any electronic or electrical equipment
- Easy installation
- Ordering no. 90KA700

KK252ST - Keypad Knob, Silver Inlay



- Size: Triangle 45mm
- Power: 123A Lithium Battery
- Retrofits all Cylinder Lock applications
- Installation is easy as the installation of a standard mechanical
- Cylinder Lock
- Polished Chrome finished with blue back light
- Ordering no. 90KK252ST

KS300ST/GL - Knob Set (Inside and Outside)



- Size: Triangle 45mm
- Power: 123A Lithium Battery
- Retrofits all Cylinder Lock applications
- Installation is easy as the installation of a standard mechanical
- Cylinder Lock
- KS300ST : Polished Chrome finished
- KS300GL : Gold Plated finished

MK202ST/GL - Mounted Keypad



- Wireless keypad
- Size: 130mm, 60mm, 23mm
- Back Light: Blue
- Power: 1 or 2 x 123A Lithium Batteries
- Door or frame mounted (indoor only) for use with Door

locks or Drawer Locks.

- Recommended for commercial applications: Offices, warehouses, airports, hospitals, public buildings, etc. (no need to carry a KnockKey)
- MK202ST : Polished Chrome finished
- MK202GL : Gold Plated finished
- Ordering no. 90MK202ST / 90MK202GL

PK116BL - KnockKey, Black, Black Inlay



- Size: 56mm, 32mm, 19mm
- Keypad: Tactile Switches, Black
- Back Light: Yellow
- Power: CR2 Lithium Battery
- Any wood or metal doors
- Easy installation, no need to drill thru holes in the door
- PC programmable in HD455 model
- Maximum security - no physical access to lock from outside
- Ordering no. 90PK116BL

PK117CR - KnockKey, Black, Black Inlay



- Size: 56mm, 32mm, 19mm
- Keypad: Tactile Switches, Black
- Back Light: Yellow
- Power: CR2 Lithium Battery
- PTT: Programmable To Transmit -pre-programmed code automatic transmission function
- Recommended for consumer and commercial applications
- Ordering no. 90PK117CR

SD460Y - Versatile Lock Low Temp Operation



- Size: 185mm, 32mm, 30mm
- Finish: Silver Aluminum
- Power, 123A Lithium Battery
- Minimum recommended temperature: -20°C
- All types of cabinets, containers, or doors
- Maximum security- no physical access to lock from outside
- Odering no.90SD460Y

SD465 - Versatile Lock



- Size: 185mm, 32mm, 30mm
- Finish: Silver Aluminum
- Power, 123A Lithium Battery
- Accessories : different types of brackets and strikes
- Minimum recommended temperature: -20°C.
- All types of cabinets, containers, or doors
- Maximum security - no physical access to lock from outside
- PC programmable model in SD465
- Low Temperature Operation model in SD465Y
- Ordering no. 90SD465

SD465Y - Versatile Lock



- Size: 185mm, 32mm, 30mm
- Finish: Silver Aluminum
- Power, 123A Lithium Battery
- Accessories : different types of brackets and strikes
- Minimum recommended temperature: -20°C.
- All types of cabinets, containers, or doors
- Maximum security - no physical access to lock from outside
- PC programmable model in SD465
- Low Temperature Operation model in SD465Y
- Ordering no. 90SD465Y

Guard Moinitering Units

AS

ACTIVE- GUARD - Real Time Guard Tour System



- Real Time -Time and Attendance Solution via RFID
- Real Time -GSM/GPRS Panic Button
- Low cost of GPRS transmission
- Voice Capability through "Call Me" function
- Real Time RFID Guard Tracking solution
- Real Time Operator Activity Management
- Real Time and Historic Reporting functionality, On or Off Site
- Ordering no. 48ACTIVE-GUARD



ANTODB - Antenna 0DB

- 0Db 50 Ohm GSM/GPRS 900-1800Mhz Antenna
- 1.5 m cable
- SMA Connector
- Ordering no. 48ANTODB

Door Closers

VISIONLINE

U503B - VisionLine Bronze Door Closer



- Apply to various commercial doors
- Popular European style cast aluminum body
- Complied with CE:EN 1154 performance and EN1634 fire test
- U503B : Bronze Door Closer (Medium Duty)
- Ordering no. 80U503B

U503S - Door Closers



- Apply to various commercial doors
- Popular European style cast aluminum body
- Complied with CE:EN 1154 performance and EN1634 fire test
- U503S : Silver Door Closer (Medium Duty)
- Ordering no. 80U503S

U504G - Door Closers



- Apply to various commercial doors
- Popular European style cast aluminum body
- Complied with CE:EN 1154 performance and EN1634 fire test
- U504G : Grey Door Closer (Heavy Duty)
- Odering no.80 U504G

Striker Locks

VISIONLINE



A201 - Striker Lock

- Volt Operational
- Pulse Striker Lock model - N201
- Continues Striker Lock model - A201
- Ordering no. 77N201



N201 - Striker Lock

- Volt Operational
- Pulse Striker Lock model - N201
- Continues Striker Lock model - A201
- Ordering no. 77A201

Magnetic Locks

VISIONLINE

BEL-1200LED - 1200lbs Electro Magnetic Lock with LED



- 1200lbs holding force
- Input voltage: 12/24VDC
- Current draw: 420/210mA
- Mounting type: Surface
- Lock dimension: 266 x 67 x 30mm
- Armature dimension: 185 x 61 x 16.5mm
- Built-in: Magnetic bond-sensor, LED, NC/NO, jumper selector
- Ordering no. 78BEL1200LED

BEL-300S - BEL-300SBEL-300S



- 300lbs holding force
- Input voltage: 12/24VDC
- Current draw: 300/150mA
- Mounting type: Surface
- Lock dimension: 170 x 35 x 21mm
- Armature dimension: 130 x 33 x 11mm
- Ordering no. 78BEL-300S

BEL-600LED - 550lbs Electro Magnetic Lock with LED



- 550lbs holding force
- Input voltage: 12/24VDC
- Current draw: 480/240mA
- Mounting type: Surface
- Lock dimension: 250 x 42 x 25mm
- Armature dimension: 180 x 38 x 11mm
- Built-in: Magnetic bond-sensor, LED, NC/NO, jumper selector
- Ordering no. 78BEL600LED

BEL-600M - 550lbs Electro Mortice Lock



- 550lbs holding force
- Input voltage: 12/24VDC
- Current draw: 480/240mA
- Mounting type: Concealed
- Lock dimension: 230 x 38 x 26mm
- Built-in: Reed switch
- Ordering no. 78BEL600M

BEL-600S - 550 lbs Electro Magnetic Lock



- 550lbs holding force
- Input voltage: 12/24VDC
- Current draw: 480/240mA
- Mounting type: Surface
- Lock dimension: 250 x 42 x 25mm
- Armature dimension: 180 x 38 x 11mm
- Built-in: Terminal block, jumper selector
- Ordering no. 78BEL-600S

L1-300S/ 600S - Bracket for Sliding Doors



- Mounting bracket for sliding door with magnetic lock BEL-300lbs / BEL-600lbs
- Ordering no. 78L1-300S / 78L1-600S

LS-300S/ 600S/ 1200S - Bracket for Door with Narrow Head



- Mounting bracket for swing door where the header is too narrow with magnetic lock BEL-300lbs / BE
- Ordering no. 78LS-300S / 78LS-600S / 78LS-1200S

U1-300S/ 600S/ 1200S - Bracket for Frameless Glass Doors



- Mounting bracket for glass door with magnetic lock BEL-300lbs / BEL-600lbs / BEL-1200lbs
- Ordering no. 78U1-300S / 78U1-600S / 78U1-1200S

ZL-300S/ 600S/ 1200S - Z-Bracket for in swing doors



- Mounting bracket for in-swing door with magnetic lock BEL-300lbs / BEL-600lbs / BEL-1200lbs
- Ordering no. 78ZL-300S / 78ZL-600S / 78ZL1200S

BEL-1200LED - 1200lbs Electro Magnetic Lock with LED

- 1200lbs holding force
- Input voltage: 12/24VDC
- Current draw: 420/210mA
- Mounting type: Surface
- Lock dimension: 266 x 67 x 30mm
- Armature dimension: 185 x 61 x 16.5mm
- Built-in: Magnetic bond-sensor, LED, NC/NO, jumper selector
- Ordering no. 78BEL1200LED

BEL-300S - BEL-300SBEL-300S

- 300lbs holding force
- Input voltage: 12/24VDC
- Current draw: 300/150mA
- Mounting type: Surface
- Lock dimension: 170 x 35 x 21mm
- Armature dimension: 130 x 33 x 11mm
- Ordering no. 78BEL-300S

BEL-600LED - 550lbs Electro Magnetic Lock with LED

- 550lbs holding force
- Input voltage: 12/24VDC
- Current draw: 480/240mA
- Mounting type: Surface
- Lock dimension: 250 x 42 x 25mm
- Armature dimension: 180 x 38 x 11mm
- Built-in: Magnetic bond-sensor, LED, NC/NO, jumper selector
- Ordering no. 78BEL600LED

BEL-600M - 550lbs Electro Mortice Lock

- 550lbs holding force
- Input voltage: 12/24VDC
- Current draw: 480/240mA
- Mounting type: Concealed

- Lock dimension: 230 x 38 x 26mm
- Built-in: Reed switch
- Ordering no. 78BEL600M

BEL-600S - 550 lbs Electro Magnetic Lock



- 550lbs holding force
- Input voltage: 12/24VDC
- Current draw: 480/240mA
- Mounting type: Surface
- Lock dimension: 250 x 42 x 25mm
- Armature dimension: 180 x 38 x 11mm
- Built-in: Terminal block, jumper selector
- Ordering no. 78BEL-600S

L1-300S/ 600S - Bracket for Sliding Doors



- Mounting bracket for sliding door with magnetic lock BEL-300lbs / BEL-600lbs
- Ordering no. 78L1-300S / 78L1-600S

LS-300S/ 600S/ 1200S - Bracket for Door with Narrow Head



- Mounting bracket for swing door where the header is too narrow with magnetic lock BEL-300lbs / BE
- Ordering no. 78LS-300S / 78LS-600S / 78LS-1200S

U1-300S/ 600S/ 1200S - Bracket for Frameless Glass Doors



- Mounting bracket for glass door with magnetic lock BEL-300lbs / BEL-600lbs / BEL-1200lbs
- Ordering no. 78U1-300S / 78U1-600S / 78U1-1200S



ZL-300S/ 600S/ 1200S - Z-Bracket for in swing doors

- Mounting bracket for in-swing door with magnetic lock BEL-300lbs / BEL-600lbs / BEL-1200lbs
- Ordering no. 78ZL-300S / 78ZL-600S / 78ZL1200S

Power Supplies

AS



71120-20 - 12V DC 1.2 Amp Power Pack

- Supplied without the 12V 7AH sealed battery
- Dimensions: 230 x 160 x 80 mm (L x W x H)
- Ordering no. 71120-20



71120-30 - 12V DC 3 Amp Power Pack

- Input Voltage 220V AC - 50 Hz
- Output 12V 1.2 Amp
- 2 Cable Glands & Mains LED Indicator
- Battery Low Indicator
- External Fuse